

ASTM F 718

SHIPBUILDERS AND MARINE PAINTS AND COATINGS PRODUCT/PROCEDURE DATA SHEET

CONTINUATION SHEET USED: YES NO

Date: 08/11/2010 Rev. 010-1

I. GENERIC TYPE AND DESCRIPTION: **SYNTHETIC SKID RESISTANCE AGGREGATE**

Specification Number, Type, Class and/or Grade (If Applicable): **MIL-PRF-24613, TYPE I CLASS 3**

II. MANUFACTURERS DATA:

- (a) MANUFACTURER: **CROSSFIELD PRODUCT CORP.
DEX-O-TEX MARINE PRODUCT LINE**
- (b) PRODUCT DESIGNATION: **1765**
- (c) COLOR(S): **Translucent granules**
- (d) USES: **Ant-skid additive to sealers**
- (e) TECHNICAL SERVICE REPRESENTATIVE
(Include Telephone Nos.): **STEVEN SCHROEDER 310-886-9100 (www.dexotexmarine.com)**
- (f) NOT RECOMMENDED FOR: **N/A**

III. PROPERTIES:

- (a) % VOLUME SOLIDS (ASTM D 2697): **100%**
- (b) % WEIGHT SOLIDS (ASTM D 1475): **100%**
- (c) FLASH POINT (ASTM TEST METHOD D 93 OR D 56 OR D 3278): **N/A**
- (d) WEIGHT PER VOLUME: (FTMS 141a4184.1): **3.6 lbs. / gallon**
- (e) % EDGE RETENTION (IF REQUIRED BY APPLICABLE SPECIFICATION): **N/A**
- (f) SHELF LIFE: **One year from the date of manufacture**
- (g) VISCOSITY: **Solid material**
- (h) PACKAGING: **1 gallon can**
- (i) NUMBER OF COMPONENTS: **One**
- (j) GLOSS (ASTM D 523): **N/A** (NOTE: This is to be a percentage, not "Gloss," "Semi-gloss," etc.) – **N/A**
- (k) STORAGE REQUIREMENTS: TEMP. MIN.: **65°F** MAX.: **75°F**
ADDITIONAL PAINT STORAGE REQUIREMENTS: **Dry Area. Not in direct sunlight.**
- (l) VOLATILE ORGANIC COMPOUND (EPA TEST METHOD 24): **N/A**
- (m) WEIGHT OF DRY FILM (WEIGHT/FT² AT 1 MIL THICKNESS): **N/A**
- (n) SPECIAL PROPERTIES (e.g., STAIN RESISTANCE, LOW SOLAR ABSORBANCE, MOISTURE TOLERANCE): **N/A**

IV. SURFACE PREPARATION MINIMUM REQUIREMENTS (USE SPECIFIC STANDARD NUMBERS):

**Surface profile is in accordance with SSPC-PC 1 and SSPC-PC 2
Dex-O-Tex Terracolor may be applied to a cured Navy Formula 150 Primer, MIL-DTL-24441.**

- (a) INITIAL – **N/A**
- (b) TOUCH-UP – **N/A**
- (c) PROFILE (INCLUDE METHOD USED) – **N/A**
- (d) SPECIAL INSTRUCTIONS – **N/A**
- (e) PRIMER REQUIREMENTS (IF APPLICABLE): **N/A**
- (f) MAXIMUM ALLOWABLE CONDUCTIVITY (BRESLE PATCH METHOD): Refer to NAVSEA Standard Item 009-32
- (g) MAXIMUM DEGREE OF FLASH RUSTING ALLOWABLE (LIST COMMERCIAL STANDARD): **N/A**

SPECIAL SAFETY PRECAUTIONS:

**Use good ventilation, avoid breathing vapors and use a fan to circulate fresh air.
Always obtain, read and observe Manufacturers Material Safety Data Sheet**

ASTM F 718 CONTINUATION SHEET FOR
SHIPBUILDERS AND MARINE PAINTS AND COATINGS PRODUCT/PROCEDURE DATA SHEET

Date: 08/11/2010 Rev. 010-1

I. GENERIC TYPE AND DESCRIPTION: N/A
Specification Number (If Applicable): N/A

ADDITIONAL DATA/ INSTRUCTIONS: N/A

II. MANUFACTURERS DATA: N/A

ADD ADDITIONAL COMMENTS FROM PART II HERE: N/A

III. PROPERTIES: N/A

ADD ADDITIONAL COMMENTS FROM PART III HERE: N/A

IV. SURFACE PREPARATION MINIMUM REQUIREMENTS (USE SPECIFIC STANDARD NUMBERS): N/A

ADD ADDITIONAL COMMENTS FROM PART IV HERE: N/A

V. MIXING PROCEDURES: N/A

ADD ADDITIONAL COMMENTS FROM PART V HERE: N/A

VI. APPLICATION REQUIREMENTS: N/A

ADD ADDITIONAL COMMENTS FROM PART VI HERE: N/A