

ASTM F 718

SHIPBUILDERS AND MARINE PAINTS AND COATINGS PRODUCT/PROCEDURE DATA SHEET

CONTINUATION SHEET USED: YES NO

Date: 7/15/2009 Rev.010-1

I. GENERIC TYPE AND DESCRIPTION: **TERRAZZO M CLEARSEALER Unit 1**

Specification Number, Type, Class and/or Grade (If Applicable): **MIL-D-3134, TYPE I, CLASS 2**
MIL-PRF-24613, TYPE I, CLASS 3

II. MANUFACTURERS DATA:

- (a) MANUFACTURER: **CROSSFIELD PRODUCTS CORP.**
DEX-O-TEX MARINE PRODUCT LINE
- (b) PRODUCT DESIGNATION: **1422 - Component G**
1423 - Component H
- (c) COLOR(S): **CLEAR**
- (d) USES: **CLEARSEALER**
- (e) TECHNICAL SERVICE REPRESENTATIVE
 (Include Telephone Nos.): **STEVEN SCHROEDER 310-886-9100**
- (f) NOT RECOMMENDED FOR: **N/A**

III. PROPERTIES:

- (a) % VOLUME SOLIDS (ASTM D 2697): **100%**
- (b) % WEIGHT SOLIDS (ASTM D 1475): **100%**
- (c) FLASH POINT (ASTM TEST METHOD D 93 OR D 56 OR D 3278): **N/A**
- (d) WEIGHT PER VOLUME: (FTMS 141a4184.1): **N/A**
- (e) % EDGE RETENTION (IF REQUIRED BY APPLICABLE SPECIFICATION): **N/A**
- (f) SHELF LIFE: **One year from date of manufacture**
- (g) VISCOSITY (STATE TEST METHOD TO BE USED: ASTM D445): **N/A**
- (h) PACKAGING: **1422 - Component G (5 pound can)**
1423 - Component H (2.5 pound can)
- (i) NUMBER OF COMPONENTS: **Two (2)**
- (j) GLOSS (ASTM D 523): (NOTE: This is to be a percentage, not "Gloss," "Semi-gloss," etc.) – **N/A**
- (k) STORAGE REQUIREMENTS: TEMP. MIN. **65° F** MAX. **80° F**
 ADDITIONAL PAINT STORAGE REQUIREMENTS: **Store in cool, dry environment, out of direct sunlight.**
- (l) VOLATILE ORGANIC COMPOUND (EPA TEST METHOD 24): **N/A**
- (m) WEIGHT OF DRY FILM (WEIGHT/FT² AT 1 MIL THICKNESS): **N/A**
- (n) SPECIAL PROPERTIES (e.g., STAIN RESISTANCE, LOW SOLAR ABSORBANCE, MOISTURE TOLERANCE): **None**

IV. SURFACE PREPARATION MINIMUM REQUIREMENTS (USE SPECIFIC STANDARD NUMBERS):

Refer to NAVSEA Standard Item 009-32

- (a) INITIAL – **N/A**
- (b) TOUCH-UP - **N/A**
- (c) PROFILE (INCLUDE METHOD USED) – **N/A**
- (d) SPECIAL INSTRUCTIONS – **N/A**
- (e) PRIMER REQUIREMENTS (IF APPLICABLE): **N/A**
- (f) MAXIMUM ALLOWABLE CONDUCTIVITY (BRESLE PATCH METHOD): Refer to NAVSEA Standard Item 009-32: **N/A**
- (g) MAXIMUM DEGREE OF FLASH RUSTING ALLOWABLE (LIST COMMERCIAL STANDARD): **N/A**

SPECIAL SAFETY PRECAUTIONS:

Use good ventilation, Avoid breathing vapors, use a fan to circulate fresh air.
Always obtain, read and observe Manufacturer's Material Safety Data Sheets before handling polymeric materials.

ASTM F 718 CONTINUATION SHEET FOR

SHIPBUILDERS AND MARINE PAINTS AND COATINGS PRODUCT/PROCEDURE DATA SHEET

Date: 7/15/2009 Rev.010-1

I. GENERIC TYPE AND DESCRIPTION: N/A
Specification Number (If Applicable): N/A

ADDITIONAL DATA/ INSTRUCTIONS: N/A

II. MANUFACTURERS DATA: N/A

ADD ADDITIONAL COMMENTS FROM PART II HERE: N/A

III. PROPERTIES: N/A

ADD ADDITIONAL COMMENTS FROM PART III HERE: N/A

IV. SURFACE PREPARATION MINIMUM REQUIREMENTS (USE SPECIFIC STANDARD NUMBERS): N/A

ADD ADDITIONAL COMMENTS FROM PART IV HERE: N/A

V. MIXING PROCEDURES: N/A

ADD ADDITIONAL COMMENTS FROM PART V HERE: N/A

VI. APPLICATION REQUIREMENTS: N/A

ADD ADDITIONAL COMMENTS FROM PART VI HERE: N/A