



Specification Reference

MIL-D-3134, Type II, Class 1
MARAD Spec No. 59MA-7

Dex-O-Tex Neotex 28 Marine Decking Product Description Sheet

TYPE

Neotex 28 is a deck covering material for use on weather exposed decks or on interior service areas. It is a Neoprene Latex Mastic which is trowel applied to form a jointless surface, including ship's cove or sanitary base. Neotex 28 is applied directly to the deck surface and will form its own bond without the use of mechanical anchors. Due to its exceptionally good adhesion, its resistance to cracking and waterproof properties, it will provide lasting protection from rust and corrosion to the metal deck surfaces to which it is applied. Dex-O-Tex Neotex 28 has good weather resistance and will not become soft with heat nor brittle when cold. It is durable under traffic when constantly wet and is resistant to a wide range of acids and many chemicals.

TECHNICAL DATA

Weight 2.35 lbs/ft² @ 1/4 inch
(11.47 kg/m² @ 6.35 mm)

Indentation Resistance 2,000 psi @ 1/2 hr
(3% average) (288,000 lbs/ft²)
(140,614 kg/m²)

Adhesive Strength, Shear 150 psi
(21,600 lbs/ft²)
(105,460 kg/m²)

Corrosive Effect, Steel None

Corrosive Effect, Aluminum None

Flow at Elevated Temperature None
(200°F/93°C @ 4 hrs)

Fire Rating U.S. Navy Fire Retardant

SPECIFICATION REFERENCE

U.S. Dept.
of Defense MIL-D-3134, Type II, Class 1

U.S. Dept.
of Defense MARAD Spec No. 59MA-7

TYPICAL USES

- Exterior deck surfacing
- Service passageways
- Shower, washroom & toilet spaces
- Refrigerator floor
- Some food & preparation areas

THICKNESS

1/4 inch (6.35 mm) minimum to
1/2 inch (12.7 mm)

ADVANTAGES

- Tough and durable
- Resists weathering
- Can be applied at a range of thicknesses to cover surface irregularities
- Skid resistant
- Good impact resistance



LIMITED WARRANTY

NO WARRANTY SHALL BE EFFECTIVE UNTIL THE TERMS AND CONDITIONS OF SALE SET FORTH IN CROSSFIELD PRODUCTS CORP. INVOICES ARE MET.

Crossfield Products Corp. warrants to the purchaser of its products that such products are free from manufacturing defect. Crossfield does not warrant or guarantee the workmanship performed by any person or firm installing its products. Crossfield's obligation under this warranty is limited solely to the original purchaser and solely to the remedy of replacement in kind of any product which Crossfield sold which may prove defective in manufacture within one year from date of installation, provided said product was stored correctly and installed within the product's shelf life, by the original purchaser and which Crossfield's examination shall disclose to Crossfield's satisfaction to be thus defective.

In no event shall Crossfield Products Corp. be liable for any incidental or consequential damages. This warranty is expressly given in lieu of all other warranties expressed or implied, including the warranties of merchantability and fitness for use and all other obligations or liabilities on Crossfield's part, and we neither assume nor authorize any person or persons to assume for us any other liability in connection with sale of a Crossfield Products. This warranty shall not apply to any of Crossfield's products, which have been subject to adulteration, alteration abuse or misuse. Crossfield Products Corp. makes no warranty whatsoever in respect to accessories, parts or material not supplies by Crossfield Products Corp., which are used in connection with its products. The term "Original Purchaser" in this warranty means that person, corporation or entity to whom Crossfield Products Corp. sold its products. Any action to enforce any warranty or for breach of contract or arising out of any claim against Crossfield Products Corp. shall be commenced and maintained only in a court of competent jurisdiction in the continental United States of America. The purchaser accepts these terms and conditions and hereby expressly waives any claim to additional damages.

CAUTION: ALWAYS KEEP OUT OF THE REACH OF CHILDREN.



Dex-O-Tex Marine Product Line
Crossfield Products Corp.
www.dextotexmarine.com



West Coast Office
3000 E. Harcourt St.
Rancho Dominguez, CA 90221
Telephone • 310.886.9100
Fax • 310.886.9119

East Coast Office
140 Valley Road
Roselle Park, NJ 07204
Telephone • 908.245.2800
Fax • 908.245.0659