



Specification Reference

USCG Approval Number: 164.117/53/0
IMO Parts 2 and 5 of Annex 1 of the 2010 FTP Code
EC/US MRA Approved
USCG Approval Number: 164.106/55/0
IMO Parts 2 and 5 of Annex 1 of 2010 FTP Code
EC/US MRA Approved



Dex-O-Tex Decor-Flor M Marine Decking Product Description Sheet

TYPE

Dex-O-Tex Decor-Flor M is a thin-section seamless primary deck and floor covering comprised of attractively colored color coated quartz granules embedded in a clear, catalyst-reacted epoxy resin binder. It is applied to a thickness of approximately 1/16 inch (1.5875mm) and a cove base can be incorporated to form a continuous joint-free surface. Decor-Flor M develops an exceptionally good bond when applied directly to cleaned metal surfaces. Décor-Flor M has good resistance to water, cooking fats and greases, and will provide a durable decking for commissary spaces and interior sanitary and wet spaces. Its natural textured surface provides good slip resistance

SPECIFICATION REFERENCE

USCG Approval Number: 164.117/53/0
IMO Parts 2 and 5 of Annex 1 of the 2010 FTP Code
EC/US MRA Approved

USCG Approval Number: 164.106/55/0
IMO Parts 2 and 5 of Annex 1 of 2010 FTP Code
EC/US MRA Approved



THICKNESS

1/16 inch (1.5875mm)

TECHNICAL DATA

Weight..... 1.25 lbs/ft² @ 1/16 inch
(6.10 kg/m² @ 1.5875 mm)

Indentation Resistance..... 2,000 psi @ 1/2 hr
(1.5% average) (288,000 lbs/ft²)
(140,614 kg/m²)

Impact Resistance.....0.03 inches
(0.762 mm)
(2 lb steel ball @ 8 ft)

Moisture Absorption..... <1.4%

Fire Rating.....IMO FTP Part 5 and Part 2

Adhesive Strength, Shear 748 psi
(107,712 lbs/ft²)
(525,896 kg/m²)

Corrosive Effect, Steel..... None

Corrosive Effect, Aluminum None

TYPICAL USES

- Galleys
- Sculleries
- Bake shops
- Washrooms & Laundries
- Water closets & shower spaces
- Food preparation & service areas

ADVANTAGES

- Fast curing for short installation time
- Durable in sanitary wet space areas
- Easily maintained
- Decorative
- Fire retardant
- Slip retardant
- Not flammable or toxic in wet state



LIMITED WARRANTY

NO WARRANTY SHALL BE EFFECTIVE UNTIL THE TERMS AND CONDITIONS OF SALE SET FORTH IN CROSSFIELD PRODUCTS CORP. INVOICES ARE MET.

Crossfield Products Corp. warrants to the purchaser of its products that such products are free from manufacturing defect. Crossfield does not warrant or guarantee the workmanship performed by any person or firm installing its products. Crossfield's obligation under this warranty is limited solely to the original purchaser and solely to the remedy of replacement in kind of any product which Crossfield sold which may prove defective in manufacture within one year from date of installation, provided said product was stored correctly and installed within the product's shelf life, by the original purchaser and which Crossfield's examination shall disclose to Crossfield's satisfaction to be thus defective.

In no event shall Crossfield Products Corp. be liable for any incidental or consequential damages. This warranty is expressly given in lieu of all other warranties expressed or implied, including the warranties of merchantability and fitness for use and all other obligations or liabilities on Crossfield's part, and we neither assume nor authorize any person or persons to assume for us any other liability in connection with sale of a Crossfield Products. This warranty shall not apply to any of Crossfield's products, which have been subject to adulteration, alteration abuse or misuse. Crossfield Products Corp. makes no warranty whatsoever in respect to accessories, parts or material not supplies by Crossfield Products Corp., which are used in connection with its products. The term "Original Purchaser" in this warranty means that person, corporation or entity to whom Crossfield Products Corp. sold its products. Any action to enforce any warranty or for breach of contract or arising out of any claim against Crossfield Products Corp. shall be commenced and maintained only in a court of competent jurisdiction in the continental United States of America. The purchaser accepts these terms and conditions and hereby expressly waives any claim to additional damages.

CAUTION: ALWAYS KEEP OUT OF THE REACH OF CHILDREN.



Dex-O-Tex Marine Product Line
Crossfield Products Corp.
www.dextotexmarine.com



West Coast Office
3000 E. Harcourt St.
Rancho Dominguez, CA 90221
Telephone • 310.886.9100
Fax • 310.886.9119

East Coast Office
140 Valley Road
Roselle Park, NJ 07204
Telephone • 908.245.2800
Fax • 908.245.0659