

CROSSFIELD PRODUCTS CORPORATION

www.crossfieldproducts.com

3000 E. Harcourt St.
 Rancho Dominguez, CA 90221 (Headquarters)
 (310)-886-9100 (8:00 AM – 5:00 PM Pacific Time)

140 Valley Rd.
 Roselle Park, NJ 07204
 (908)-245-2800 (8:00 AM – 5:00 PM Eastern Time)

SAFETY DATA SHEET

1. PRODUCT IDENTIFICATION

TRADE NAME (AS LABELED):

VLW Underlay Self Prime Part B
VLW Underlay Primer Required Part B

CHEMICAL NAME/CLASS:

Polyamine Solution

PRODUCT USE:

Specialty Flooring Curative

SUPPLIER/MANUFACTURER'S NAME:

Crossfield Products Corp.

ADDRESS: (West Coast):

3000 E. Harcourt St.
 Rancho Dominguez, CA 90221 (Headquarters)

ADDRESS: (East Coast):

140 Valley Rd.
 Roselle Park, NJ 07204

EMERGENCY PHONE:

CHEMTREC: 800-424-9300

DATE OF PREPARATION:

February 23, 2022

REVISION DATE:

May 23, 2022

2. HAZARD(S) IDENTIFICATION



GHS classification

Acute toxicity – Oral Category 4
 Acute toxicity – Inhalation Category 2
 Acute toxicity – Dermal Category 4
 Skin Corrosion - Category 1B
 Serious Eye Damage - Category 1
 Skin sensitization - Category 1
 Specific target organ toxicity (single exposure) Respiratory System – Category 3

Signal Word: (Danger)

Hazard Statements:

H302+H312: Harmful if swallowed or in contact with skin
 H314: Causes severe skin burns and eye damage
 H317: May cause an allergic skin reaction

H330: Fatal if inhaled
 H335: May cause respiratory irritation

Precautionary Statements:

P102: Keep out of reach of children
 P103: Read label before use
 P260 Do not breathe dust/fume/gas/mist/vapors/spray
 P264: Wash hands thoroughly after handling
 P280: Wear protective gloves/protective clothing/eye protection/face protection
 P284: Wear respiratory protection
 P301+P312: IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell
 P301+P330+P331: IF SWALLOWED: rinse mouth. Do not induce vomiting
 P303+P361+P353: IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower
 P304+P340:
 P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
 P310: Immediately call a POISON CENTER or doctor/physician
 P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

P363: Wash contaminated clothing before reuse
 P403+P233: Store in a well-ventilated place. Keep container tightly closed.
 P501: Dispose of contents and container in accordance with all local, regional, national and international regulations.

Hazards not otherwise classified

This product contains a component that is toxic by inhalation when aerosolized or sprayed. Please refer to Section 11 of the SDS for toxicity information. Review the toxicity information against your intended use. If product is not being aerosolized or sprayed, the inhalation toxicity may not be applicable.

- Harmful if swallowed
- Corrosive
- May cause sensitization by skin contact
- Harmful in contact with skin
- Very toxic by inhalation
- Respiratory irritant

50% of mixture consists of ingredients of unknown acute toxicity.

HMIS-RATINGS (SCALE 0 – 4)

HEALTH	3
FLAMMABILITY	1
REACTIVITY	0

Health = 3
 Fire = 1
 Reactivity = 0

NFPA RATING



3. COMPOSITION / INFORMATION ON INGREDIENTS

CHEMICAL NAME	CAS #	% w/w	EXPOSURE LIMITS IN AIR					
			ACGIH		OSHA		IDLH mg/m ³	OTHER mg/m ³
			TLV mg/m ³	STEL mg/m ³	PEL mg/m ³	STEL mg/m ³		
Diethylene Triamine (DETA)	111-40-0	15 - 40	8 hr TWA 1 ppm	NE	8 hr TWA 1 ppm 4 mg/m ³	NE	NE	NIOSH 10 hr TWA 1 ppm 4 mg/m ³
Formaldehyde, polymer with 1,3, dimethylbenzene	26139-75-3	0.1 - 1						
Water and other ingredients. The other ingredients are each present in less than 1 percent concentration in this product.		Balance	The components present in the balance of this product do not contribute any significant, additional hazards. All hazard information pertinent to this product has been presented in the remaining sections of this Material Safety Data Sheet, per the requirements of Federal Occupational Safety and Health Hazard Communication Standard (29 CFR 1910.1200).					
VOC: Component = 0 Grams/Liter			As Applied – 0 Grams/Liter (Part of Multi-Component System)					

NE = Not Established. C = Ceiling Limit. See Section 16 for Definitions of Terms Used.
 NOTE: All WHMIS required information is included. It is located in appropriate sections based on the ANSI Z400.1-1993 format.

4. FIRST-AID MEASURES

- General advice:** Seek medical advice. If breathing has stopped or is labored, give assisted respirations. Supplemental oxygen may be indicated. If the heart has stopped, trained personnel should begin cardiopulmonary resuscitation immediately.
- Eye contact:** Hold eyelids apart, initiate and maintain gently and continuous irrigation until the patient receives medical care. If medical care is not promptly available, continue to irrigate for one hour. Rinse immediately with plenty of water also under the eyelids for one hour.
- Skin contact:** Immediately remove contaminated clothing, and any extraneous chemical, if possible to do so without delay. Initiate and maintain continuous irrigation until the patient receives medical care. If medical care is not promptly available, continue to irrigate for one hour. Cover wound with sterile dressing. Take off contaminated clothing and shoes immediately. **NOTE TO PHYSICIANS:** Application of corticosteroid cream has been effective in treating skin irritation.

Ingestion: If a person vomits when lying on his back, place him in the recovery position. Never give anything by mouth to an unconscious person. Prevent aspiration of vomit. Turn victim's head to the side.

Inhalation: If breathing has stopped or is labored, give assisted respirations. Supplemental oxygen may be indicated. If the heart has stopped, trained personnel should begin cardiopulmonary resuscitation immediately. Move to fresh air.


Most important Symptoms/effects-acute and delayed: Repeated and/or prolonged exposure to low concentrations of vapors and/or aerosols may cause: Sore throat, Asthma, Eye disease, Kidney disorders, Liver disorders, Skin disorders and allergies.

5. FIRE-FIGHTING MEASURES

FLASH POINT, °C (method): 110°C (230°F) Closed Cup
AUTOIGNITION TEMPERATURE, °C: ND
FLAMMABLE LIMITS (in air by volume, %):

Lower (LEL): NE
Upper (UEL): NE

NFPA RATING



FIRE EXTINGUISHING MATERIALS:

Water Spray: YES
Foam: YES
Halon: ND

Carbon Dioxide: YES
Dry Chemical: YES
Other: Any "ABC" Class.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Run-off from fire control may cause pollution. Keep fire-exposed containers cool with water spray to prevent rupture due to excessive heat. High pressure water hose may spread product from broken containers increasing contamination. If involved in a fire, this product may decompose to produce a variety of compounds (i.e. carbon monoxide, carbon dioxide, aldehydes, nitrogen oxides and compounds). Emergency responders must wear the proper personal protective equipment suitable for the situation to which they are responding. Products of combustion are irritating to the respiratory tract and may cause breathing difficulty. Symptoms may be delayed several hours or longer depending upon the extent of exposure.

Explosion Sensitivity to Mechanical Impact: Not sensitive.
Explosion Sensitivity to Static Discharge: Not sensitive.

SPECIAL FIRE-FIGHTING PROCEDURES: Incipient fire responders should wear eye protection. Structural fire fighters must wear Self-Contained Breathing Apparatus and full protective equipment. Move fire-exposed containers, if it can be done without risk to firefighters. If possible, prevent run-off water from entering storm drains, bodies of water, or other environmentally sensitive areas. If necessary, discard or decontaminate fire response equipment before returning such equipment to service.

6. ACCIDENTAL RELEASE MEASURES

SPILL AND LEAK RESPONSE: Uncontrolled releases should be responded to by trained personnel using pre-planned procedures. Proper protective equipment should be used. In case of a spill, clear the affected area, protect people, and respond with trained personnel.

The proper personal protective equipment for incidental releases (e.g.-1 L of the product released in a well-ventilated area) use impermeable gloves, specific for the material handled, goggles, face shield, and appropriate body protection. In the event of a large release, use impermeable gloves, specific for the material handled, chemically resistant suit and boots, and hard-hat. Self Contained Breathing Apparatus or respirator may be required where engineering controls are not adequate or conditions for potential exposure exist. When respirators are required, Select NIOSH/MSHA approved based on actual or potential airborne concentrations in accordance with latest OSHA and/or ANSI recommendations. Absorb spilled liquid with polypads or other suitable absorbent materials. Neutralize residue with sodium bicarbonate and water rinse. Decontaminate the area thoroughly. Test area with litmus paper to confirm neutralization. Place all spill residue in a suitable container. Dispose of in accordance with Federal, State, and local hazardous waste disposal regulations (see Section 13, Disposal Considerations).

7. HANDLING and STORAGE

WORK PRACTICES AND HYGIENE PRACTICES: As with all chemicals, avoid getting this product ON YOU or IN YOU. Wash hands after handling this product. Do not eat or drink while handling this material. Remove contaminated clothing immediately. Discard contaminated clothing items, or launder before re-use. Inform anyone handling such contaminated laundry of the hazards associated with this product. Use ventilation and other engineering controls to minimize potential exposure to this product.

STORAGE AND HANDLING PRACTICES: Do not store near acids. Keep containers tightly closed in a dry, cool and well-ventilated space, preferably outdoors, above ground, and surrounded by dikes to contain spills. All employees who handle this material should be trained to handle it safely. Avoid breathing mists or sprays generated by this product. Use in a well-ventilated location.

For Non-Bulk Containers: Open containers slowly, on a stable surface. Containers of this product must be properly labeled. Store containers in a cool, dry location, away from direct sunlight, sources of intense heat, or where freezing is possible. Material should be stored in secondary containers, or in a diked area, as appropriate. Store containers away from incompatible chemicals. Keep container tightly closed when not in use. Wash thoroughly after using this material. Storage areas should be made of fire-resistant materials. If appropriate, post warning signs in storage and use areas. Inspect all incoming containers before storage, to ensure containers are properly labeled and not damaged. Empty containers may contain residual liquid, therefore, empty containers should be handled with care.

Bulk Containers: All tanks and pipelines which contain this material must be labeled. Perform routine maintenance on tanks or pipelines which contain this product. Report all leaks immediately to the proper personnel.

Tank Car Shipments: Tank cars carrying this product should be loaded and unloaded in strict accordance with tank-car manufacturer's recommendation and all established on-site safety procedures. Appropriate personal protective equipment must be used (see Section 8, Engineering Controls and Personal Protective Equipment.). All loading and unloading equipment must be inspected, prior to each use. Loading and unloading operations must be attended, at all times. Tank cars must be level, brakes must be set or wheels must be locked or blocked prior to loading or unloading. Tank car (for loading) or storage tank (for unloading) must be verified to be correct for receiving this product and be properly prepared, prior to starting the transfer operations. Hoses must be verified to be clean and free of incompatible chemicals, prior to connection to the tank car or vessel. Valves and hoses must be verified to be in the correct positions, before starting transfer operations. A sample (if required) must be taken and verified (if required) prior to starting transfer operations. All lines must be blown-down and purged before disconnecting them from the tank car or vessel.

PROTECTIVE PRACTICES DURING MAINTENANCE OF CONTAMINATED EQUIPMENT: Follow practices indicated in Section 6 (Accidental Release Measures). Make certain application equipment is locked and tagged-out safely. Always use this product in areas where adequate ventilation is provided. Decontaminate equipment before maintenance begins by a triple-rinse with water followed, if necessary, by using sodium bicarbonate and an additional rinse. Collect all rinsates and dispose of according to applicable Federal, State, or local procedures.

8. EXPOSURE CONTROL/PERSONAL PROTECTION

VENTILATION AND ENGINEERING CONTROLS: If required use a corrosion-resistant ventilation system separate from other exhaust ventilation systems to ensure that there is no potential for overexposure to sprays, or mists of this product and that exposures are below those in section 2 (Composition and Information on Ingredients). Ensure eyewash/safety shower stations are available near areas where this product is used.

RESPIRATORY PROTECTION: Maintain airborne contaminant concentrations below exposure limits listed in Section 2 (Composition and Information on Ingredients). If respiratory protection is needed, use only protection authorized in 29 CFR 1910.134, or applicable State regulations. If adequate ventilation is not available or if there is potential for airborne exposure above the exposure limits (listed in Section 2) a respirator may be worn up to respirator exposure limitations, check with respirator equipment manufactures recommendations/limitations. For a higher level of protection use positive pressure supplied air respiration protection or Self Contained Breathing Apparatus or if oxygen levels are below 19.5% or are unknown.

EMERGENCY OR PLANNED ENTRY INTO UNKNOWN CONCENTRATIONS OR IDLH CONDITIONS:

Positive pressure, full-facepiece Self Contained Breathing Apparatus; or positive pressure, full-facepiece Self Contained Breathing Apparatus with an auxiliary positive pressure Self Contained Breathing Apparatus.

EYE PROTECTION: Splash goggles or safety glasses. Face-shields are recommended when the operation can generate splashes, sprays or mists.

HAND PROTECTION: Wear appropriate gloves for routine industrial use. Use appropriate gloves for spill response, as stated in Section 6 of this MSDS (Accidental Release Measures).

BODY PROTECTION: Use body protection appropriate for task. Cover-all, rubber aprons, or chemical protective clothing made from natural rubber are generally acceptable, depending upon the task.



Vapor Respirator



Safety Glasses



Safety Gloves



Synthetic Apron

9. PHYSICAL and CHEMICAL PROPERTIES

RELATIVE VAPOR DENSITY (air = 1): ND

SPECIFIC GRAVITY (water = 1): 1.09

SOLUBILITY IN WATER: Slightly soluble

VAPOR PRESSURE, mm Hg @ 21 °C: <1.00

ODOR: Amine

LOG WATER/OIL DISTRIBUTION COEFFICIENT: Not available.

EVAPORATION RATE (n-BuAc=1): ND

MELTING/FREEZING POINT: Not established.

BOILING POINT: >199°C (390°F)

pH: Not Established (Alkaline)

APPEARANCE AND COLOR: This product is an amber liquid solution.

HOW TO DETECT THIS SUBSTANCE (warning properties): ND

10. STABILITY and REACTIVITY

STABILITY: Stable under normal conditions.

DECOMPOSITION PRODUCTS: Thermal decomposition products of this solution can include a variety of compounds. (i.e. Nitric acid, Ammonia, Nitrogen Oxides, Carbon Monoxide and other compounds).

MATERIALS WITH WHICH SUBSTANCE IS INCOMPATIBLE: Avoid contact with acids, reactive metals, sodium hypochlorite, peroxides, and oxidizers.

HAZARDOUS POLYMERIZATION: Will not occur by itself. Considerable exothermic reaction with epoxy resins is possible.

CONDITIONS TO AVOID: Avoid exposure or contact to extreme temperatures and incompatible chemicals.

11. TOXICOLOGICAL INFORMATION

Likely routes of exposure:

- Effects on Eye: Causes eye burns. May cause blindness. Severe eye irritation.
- Effects on Skin: Harmful in contact with skin. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Causes skin burns.
- Inhalation Effects: This product contains a component that is toxic by inhalation when aerosolized or sprayed. Please refer to Section 11 of the SDS for toxicity information. Review the toxicity information against your intended use. If product is not being aerosolized or sprayed, the inhalation toxicity may not be applicable. Inhalation of vapors and/or aerosols in high concentration may cause irritation of respiratory system. Inhalation of aerosol may cause irritation to the upper respiratory tract. May cause nose, throat, and lung irritation. Can cause severe eye, skin and respiratory tract burns. Highly toxic by inhalation.
- Ingestion Effects: Harmful if swallowed. If ingested, severe burns of the mouth and throat, as well as a danger of perforation of the oesophagus and the stomach.
- Symptoms: Repeated and/or prolonged exposure to low concentrations of vapors and/or aerosols may cause: sore throat, Asthma, Eye disease, Kidney disorders, Liver disorders, Skin disorders and allergies.

Diethylenetriamine (111-40-0)

Acute Oral Toxicity	LD50: 1,080 mg/kg	(Species – Rat) Remarks: Behavioral: Convulsions or effect on seizure threshold.
Inhalation:	LC50 (4h): 0.3 mg/l	(Species – Rat) Remarks: Lungs, Thorax, or Respiration: Acute pulmonary edema.
Acute Dermal Toxicity	LD50: 1,090 mg/kg	(Species – Rabbit)
Skin corrosion/irritation:	Skin – Rabbit	Result: Open irritation test
Serious eye damage/eye irritation:		No data available
Respiratory or skin sensitization:		No data available
Germ cell mutagenicity:		No data available
Reproductive toxicity:		No data available
Specific target organ toxicity – single exposure		No data available
Specific target organ toxicity – repeated exposure		No data available
Aspiration hazard		No data available

Carcinogenicity:

- IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
- NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
- OSHA: No component of this product present at levels greater than or equal to 01% is identified as a carcinogen or potential carcinogen by OSHA.

Additional Information:

RTECS: IE1225000
 Material is extremely destructive to tissue of the mucous membranes and upper respiratory tract, eyes, and skin., Cough, Shortness of breath, Headache, Nausea

 Stomach – Irregularities – Based on Human Evidence

A mutagen is a chemical which causes permanent changes to genetic material (DNA) such that the changes will propagate through generational lines. An embryotoxin is a chemical which causes damage to a developing embryo (i.e. within the first eight weeks of pregnancy in humans), but the damage does not propagate across generational lines. A teratogen is a chemical which causes damage to a developing fetus, but the damage does not propagate across generational lines. A reproductive toxin is any substance which interferes in any way with the reproductive process.

12. ECOLOGICAL INFORMATION

ALL WORK PRACTICES MUST BE AIMED AT ELIMINATING ENVIRONMENTAL CONTAMINATION.

Diethylenetriamine (111-40-0)

Toxicity:	Toxicity to fish: LC50 – Poecilia reticulata (guppy)	1,014 mg/l – 96 h
Persistence and degradability	No data available	
Bioaccumulative potential	No data available	
Mobility in soil	No data available	
Results of PBT and vPvB assessment	PBT/vPvB assessment not available as chemical safety assessment not required/not conducted	
Other adverse effects	No data available	

13. DISPOSAL CONSIDERATIONS

PREPARING WASTES FOR DISPOSAL: Waste disposal must be in accordance with appropriate Federal, State, and local regulations. It may be disposed of by treatment at a permitted facility or as advised by your local hazardous waste regulatory authority.

14. TRANSPORTATION INFORMATION

Department of Transportation:

Proper Shipping Name: Paint related material
 Class: 8
 UN/ID No.: UN3066
 Packing Group: III
 Marine Pollutant: No

IATA Shipping Data:

Proper Shipping Name: Paint related material
 Class: 8
 UN/ID No.: UN3066
 Packing Group: III
 Marine Pollutant: No

IMDG Shipping Data:

Proper Shipping Name: Paint related material
 Class: 8
 UN/ID No.: UN3066
 Packing Group: III
 Marine Pollutant: No

TDG:

Proper Shipping Name: Paint related material
 Class: 8
 UN/ID No.: UN3066
 Packing Group: III
 Marine Pollutant: No

15. REGULATORY INFORMATION

OCCUPATIONAL SAFETY AND HEALTH ACT (OSHA): This Material Safety Data Sheet (MSDS) has been prepared in compliance with the federal OSHA Hazard Communication Standard 29 CFR 1910.1200.

OSHA Hazard Communication Standard (29CFR1910.1200) hazard class (es) -- Corrosive, Sensitizer.

SARA REPORTING REQUIREMENTS: The components of this product are not subject to the reporting requirements of Sections 304 and 313 of Title III of the Superfund Amendments and Reauthorization Act. Hazard classification:

Acute Health Hazard,

SARA Threshold Planning Quantity: Not applicable.

TSCA INVENTORY STATUS: The components of this product are listed on the TSCA Inventory.

CERCLA REPORTABLE QUANTITY (RQ): None

OTHER FEDERAL REGULATIONS: Not applicable.

STATE REGULATIONS

New Jersey Right-to know: The following is required composition information:

CAS Number: 111-40-0
 Chemical Name: Diethylene Triamine
 RTK No.: 0700

Pennsylvania Right-to-know: The following is required composition information:

CAS Number: 111-40-0
 Chemical Name: Diethylene Triamine

CALIFORNIA PROPOSITION 65: Not listed.

Canadian DSL: All components of this product are on the Canadian DSL.

WHMIS Classification:

D1A - Poisonous and infectious material - Immediate and serious effects – Very Toxic

D2B - Poisonous and infectious material - Other effects - Toxic

E - Corrosive material



D1A – Very Toxic



D2B – Toxic



E – Corrosive

WHMIS Health Effects Criteria Met by this Chemical:

D1A - Acute lethality – very toxic - immediate

D2B - Skin Sensitization - toxic - other

E - Corrosive to skin

E - TDG class 8 - corrosive substance

WHMIS Ingredient Disclosure List:

•Included for disclosure at 0.1% or greater.

16. OTHER INFORMATION

PREPARED BY:

BILL BEACH

CROSSFIELD PRODUCTS CORP,

THIS INFORMATION IS DRAWN FROM RECOGNIZED SOURCES BELIEVED TO BE RELIABLE. CROSSFIELD PRODUCTS CORP. MAKES NO GUARANTEES NOR ASSUMES ANY LIABILITY IN CONNECTION WITH THIS INFORMATION. THE USER SHOULD BE AWARE OF CHANGING TECHNOLOGY, RESEARCH, REGULATIONS AND ANALYTICAL PROCEDURES THAT MAY REQUIRE CHANGES HEREIN. THE ABOVE DATA IS SUPPLIED UPON THE CONDITION THAT PERSONS WILL EVALUATE THIS INFORMATION AND THEN DETERMINE ITS SUITABILITY FOR THEIR USE.

DEFINITIONS OF TERMS

A large number of abbreviations and acronyms appear on a MSDS. Some of these which are commonly used include the following:

CAS #: This is the Chemical Abstract Service Number which uniquely identifies each constituent. It is used for computer-related searching.

EXPOSURE LIMITS IN AIR:

ACGIH - American Conference of Governmental Industrial Hygienists, a professional association which establishes exposure limits.

TLV - Threshold Limit Value - an airborne concentration of a substance which represents conditions under which it is generally believed that nearly all workers may be repeatedly exposed without adverse effect. The duration must be considered, including the 8-hour **Time Weighted Average (TWA)**, the 15-minute **Short Term Exposure Limit**, and the instantaneous **Ceiling Level**. Skin adsorption effects must also be considered.

OSHA - U.S. Occupational Safety and Health Administration.

PEL - Permissible Exposure Limit - This exposure value means exactly the same as a TLV, except that it is enforceable by OSHA. The OSHA Permissible Exposure Limits are based in the 1989 PELs and the June, 1993 Air Contaminants Rule (Federal Register: 58: 35338-35351 and 58: 40191). Both the current PELs and the vacated PELs are indicated. The phrase, "Vacated 1989 PEL," is placed next to the PEL which was vacated by Court Order.

IDLH - Immediately Dangerous to Life and Health - This level represents a concentration from which one can escape within 30-minutes without suffering escape-preventing or permanent injury. **The DFG - MAK** is the Republic of Germany's Maximum Exposure Level, similar to the U.S. PEL. **NIOSH** is the National Institute of Occupational Safety and Health, which is the research arm of the U.S. Occupational Safety and Health Administration (**OSHA**). NIOSH issues exposure guidelines called Recommended Exposure Levels (**RELs**). When no exposure guidelines are established, an entry of **NE** is made for reference.

HMIS HAZARD RATINGS:

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: Health Hazard:

0 (minimal acute or chronic exposure hazard); **1** (slight acute or chronic exposure hazard); **2** (moderate acute or significant chronic exposure hazard); **3** (severe acute exposure hazard; onetime over-exposure can result in permanent injury and may be fatal); **4** (extreme acute exposure hazard; onetime over-exposure can be fatal). Flammability Hazard: **0** (minimal hazard); **1** (materials that require substantial pre-heating before burning); **2** (combustible liquid or solids; liquids with a flash point of 38-93°C [100-200°F]); **3** (Class IB and IC flammable liquids with flash points below 38°C [100°F]); **4** (Class IA flammable liquids with flash points below 23°C [73°F] and boiling points below 38°C [100°F]). Reactivity Hazard: **0** (normally stable); **1** (material that can become unstable at elevated temperatures or which can react slightly with water); **2** (materials that are unstable but do not detonate or which can react violently with water); **3** (materials that can detonate when initiated or which can react explosively with water); **4** (materials that can detonate at normal temperatures or pressures).

NATIONAL FIRE PROTECTION ASSOCIATION: Health Hazard: **0**

(material that on exposure under fire conditions would offer no hazard beyond that of ordinary combustible materials); **1** (materials that on exposure under fire conditions could cause irritation or minor residual injury); **2** (materials that on intense or continued exposure under fire conditions could cause temporary incapacitation or possible residual injury); **3** (materials that can on short exposure could cause serious temporary or residual injury); **4** (materials that under very short exposure could cause death or major residual injury). Flammability Hazard and Reactivity Hazard: Refer to definitions for "Hazardous Materials Identification System".

FLAMMABILITY LIMITS IN AIR:

Much of the information related to fire and explosion is derived from the **National Fire Protection Association (NFPA)**. Flash Point - Minimum temperature at which a liquid gives off sufficient vapors to form an ignitable mixture with air. Autoignition Temperature: The minimum temperature required to initiate combustion in air with no other source of ignition. LEL - the lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source. UEL - the highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source.

TOXICOLOGICAL INFORMATION:

Possible health hazards as derived from human data, animal studies, or from the results of studies with similar compounds are presented. Definitions of some terms used in this section are: **LD₅₀** - Lethal Dose (solids & liquids) which kills 50% of the exposed animals; **LC₅₀** - Lethal Concentration (gases) which kills 50% of the exposed animals; **ppm** concentration expressed in parts of material per million parts of air or water; **mg/m³** concentration expressed in weight of substance per volume of air; **mg/kg** quantity of material, by weight, administered to a test subject, based on their body weight in kg. Data from several sources are used to evaluate the cancer-causing potential of the material. The sources are: **IARC** - the International Agency for Research on Cancer; **NTP** - the National Toxicology Program, **RTECS** - the Registry of Toxic Effects of Chemical Substances, **OSHA** and **CAL/OSHA**. IARC and NTP rate chemicals on a scale of decreasing potential to cause human cancer with rankings from 1 to 4. Subrankings (2A, 2B, etc.) are also used. Other measures of toxicity include **TDLo**, the lowest dose to cause a symptom and **TCLo** the lowest concentration to cause a symptom; **TDo**, **LDLo**, and **LDo**, or **TC**, **TCo**, **LCLo**, and **LCo**, the lowest dose (or concentration) to cause death. **BEI** - Biological Exposure Indices, represent the levels of determinants which are most likely to be observed in specimens collected from a healthy worker who has been exposed to chemicals to the same extent as a worker with inhalation exposure to the TLV.

REGULATORY INFORMATION:

This section explains the impact of various laws and regulations on the material. **EPA** is the U.S. Environmental Protection Agency. **WHMIS** is the Canadian Workplace Hazardous Materials Information System. **DOT** and **TC** are the U.S. Department of Transportation and the Transport Canada, respectively. Other acronyms used are: **Superfund Amendments and Reauthorization Act (SARA)**; the **Toxic Substance Control Act (TSCA)**; Marine Pollutant status according to the **DOT**; California's Safe Drinking Water Act (**Proposition 65**); the **Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA or Superfund)**; and various state regulations. This section also includes information on the precautionary warnings which appear on the materials package label.